



# 3x MICROPRISM SCOPE



ALSO AVAILBLE IN FDE



## SPECIFICATIONS

MODEL NUMBER	PA-SLX-3XMP-RAPTOR-5YP	PA-SLX-3XMP-RAPTOR-5YP-G	PA-SLX-3XMP-RAPTOR-5MP	PA-SLX-3XMP-RAPTOR-7YP	PA-SLX-3XMP-RAPTOR-7YP-G	PA-SLX-3XMP-RAPTOR-5YP-FDE	PA-SLX-3XMP-RAPTOR-7YP-FDE	PA-SLX-3XMP-GRIF-MIL
MPN	710036	710037	710038	710040	710041	710054	710057	710059
MAGNIFICATION	3X MAGNIFICATION							
YARD/METER	YARDS		METERS		YARDS			METERS
OBJECTIVE LENS DIAMETER	23 MM							
EXIT PUPIL	7.4 MM							
EYE RELIEF	2.7 IN.							
TOTAL WINDAGE/ELEVATION ADJUSTMENT	80 MOA							
FIELD OF VIEW @100 YARDS	38 FT.							
ILLUMINATION	RED	GREEN	RED	RED	GREEN	RED	RED	RED
CLICK VALUE	0.25 MOA							
COLOR	BLK					FDE		BLACK
LENGTH W/O LENS COVERS	2.95 IN.							
WEIGHT W/ INCLUDED BATTERY W/O LENS COVERS	8.0 OZ.							
UPC	818500015673	818500015291	818500015796	818500015680	818500015802	818500015864	818500015871	818500018575





## RETICLE

ACSS-RAPTOR-5.56/.308-YP

ACSS-RAPTOR-7.62X39/300BO-YP

ACSS-RAPTOR-5.56/.308-MP

ACSS-GRIFFIN-X-MIL



## HIGHLIGHTS

- 13 settings; three night vision settings (NV1, NV2, NV3). Highest settings are daylight bright.
- AutoLive® motion sensing on/off technology.
- Wide field of view, excellent for CQB use.
- Accommodation for anti-reflection devices (ARD sold separately).
- Aluminum alloy main body with hard coat anodizing.
- Fully multi-coated optic.
- Nitrogen-purged.
- IP67 waterproof and dust proof.
- 8 mounting height options from 1.1" to 2.075" including absolute co-witness and lower 1/3rd options. (See next page for full options).
- Backed by our Primary Arms Lifetime Warranty.

