



Thermal Imaging Monocular Wild 650D

Technical Specifications

ThermTec Technology Co., Ltd. Email: info@thermeyetec.com Website: https://www.thermeyetec.com







WILD 650D

Key Features

- 640x512 thermal resolution, NETD<18mK;
- Aperture reaches to F#0.9 in dual field of view optical system;
- 1024*768 resolution with 0.39-inch OLED display;
- Automatic object detection and distance measurement;
- Up to 8 hours of continuous operation with lithium battery;
- Joystick control design combined with thumbwheel focus enables one-hand operation;
- Up to 64GB of storage space;
- Sunburn protection/PIP/Tracking/EIS/OSD

Applications

- Night hunting
- Observation
- Rescue operations
- Hiking and traveling

Specifications

Model	Wild650D
	Microbolometer
Resolution	640x512
Pixel Pitch	12µm
NETD	<18mK@300k
Spectral range	8-14µm
Frame rate	50HZ
Detection Range	1300m/2600m
	Optics
Objective lens	25mm/50mm
F Number	F0.9/F0.9
Field of view	17.5° x 14°/ 8.8° x 7.0°
Magnification	1.4X-2.8X
Digital Zoom	1-4X continuous zoom
Eye relief	40mm
Exit pupil	6mm
Diopter	±5D
	Display
Туре	AMOLED
Resolution	1024x768
Display size	0.39 inch
Color palette	6
Image mode	Forest/Target

	Function
Photo/video playback	Yes
Language	Multiple-languages
Inbuilt Memory	64GB
PIP	Yes
Al Distance Measurement	Yes
Heat Track	Yes
Real-time Notification	Yes
OSD Recording	Yes
Burn prevention	Yes
EIS	Yes
Internal battery	Battery Replaceable and Rechargeable Li-ion Battery (18650x1)
Battery life	8h
	Interface
Type-C	Supports battery charging, data transfer, USB video output
Hotspot	Yes, App remote control
	Environment
Working temperature	-20°C—+50°C
Protection Level	IP67
Weight, g	647.5±15
Size, mm	210*81*71
External Cable	Accessories USB cable
Other Accessories	Palm strap/Protective bag/Non-dust cloth and etc.

Accessories



Dimension

Unit: mm





