

ToLEDo Vintage G120

TOLEDO™ VINTAGE G120 250LM 820 E27 SL
0027987



Product features

- New and innovative Flexible Filament Chip Technology (FFCT) designed to create the low-lit vintage effect.
- Perfect for hotels, restaurants, heritage lighting, bars and decorative applications.
- The ideal LED solution to replace incandescent vintage globe lamps.
- Low glare - suitable for low height installation.
- 2000K colour temperature, to create a cosy ambience.
- Golden tinted glass envelope.
- 15,000 hours average rated life. Last 7.5 times longer than incandescent vintage lamps.
- Unique filament construction design - 'Helix' shape.
- Omni-directional light distribution - 300°.
- Low-lumen output to create low-lit effect - 250lm.
- More than 100,000X switching cycles.
- 3 years warranty.
- Environment friendly - no mercury and lower CO2 emissions.



PRODUCT OVERVIEW

Product name	TOLEDO™ VINTAGE G120 250LM 820 E27 SL
Technology	LED
Watt (Rated) (W)	5
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
Warranty	3 years
Useful luminous flux (Fuse)	250
Luminous flux (lm)	250
Correlated colour temperature (k)	2000
Light colour	Candlelight
Colour Code	820
CRI (Ra)	80
Beam Angle (°)	360
Power consumption (W)	5
Wattage (W)	5
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288279879

DATA TABLE

General data

Product name	TOLEDO™ VINTAGE G120 250LM 820 E27 SL
Technology	LED
Watt (Rated) (W)	5
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
Warranty	3 years

ToLEDo Vintage G120

TOLEDO™ VINTAGE G120 250LM 820 E27 SL

0027987

Optical data

Useful luminous flux (Fuse)	250
Luminous flux (lm)	250
Luminous flux (Rated) (lm)	250
Correlated colour temperature (k)	2000
Light colour	Candlelight
Colour Code	820
CRI (Ra)	80
Beam Angle (°)	360

Electrical data

Power consumption (W)	5
Wattage (W)	5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Lamp power factor	0.5
No. Of switching cycles before premature failures	>50000
Dimmable	No
Nominal Frequency (Hz)	50Hz

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	178
Nominal Product Diameter (mm)	125
Weight (kg)	0.086

Packaging

Product EAN number	5410288279879
Packaging single length / height (cm)	19.0
Packaging single width (cm)	13.0
Packaging single depth (cm)	13.0
DUN14 (inner)	15410288279876
Units per outer package	6
Packaging outer length / height (cm)	80.3
Packaging outer width (cm)	13.5
Packaging outer depth (cm)	20.0

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

ToLEDo Vintage G120

TOLEDO™ VINTAGE G120 250LM 820 E27 SL
0027987

PHOTOMETRY

TECHNICAL DRAWINGS

